

## YAEV10T3

by Burndy  
Catalog ID: YAEV10T3



Copper Terminal, Ring Tongue w/ Inspection Hole, Wire Range 12-10 AWG, 1/4" Stud, Nylon Insulated, Short Barrel, Tin Plated, 600 Volts Max.

Features: The INSULUG Type YAEV Is Designed For Very Demanding High Vibration Applications Encountered In Aircraft And Aboard Ships As Well As Motor Lead Applications In Hospitals, Industrials And Generating Plants, The Nylon Insulated Seamless, Electrolytic Copper Barrel With Double Thick Tongue Provides An Extra Strong Insulated Connection, The Terminal Is Rated 105 DEG C And Meets SAE-AS7928 Requirements, Double Thick Tongue: Provides Maximum Reliability And Electrical Capacity Plus An Extra Strong Terminal Tongue, Manufactured From One-Piece Pure Electrolytic Copper: Provides High Conductivity, Low Resistance With No Seams To Split Plus Ductility For Excellent Crimp Forming Properties, Electro-Tin Plated: Provides Long-Lasting Corrosion Resistance, Nylon Insulation Is Locked In Place: Insulation Will Not Move Or Twist Off, 300 Volt Nylon Insulation: High Dielectric Strength And Stability In Demanding Oily Environmental Conditions, Color Coded: Provides Quick, Easy Wire Size Connector Selection, #10 wire only, Temperature Rating: 105 DEG C Maximum, Package: Bulk, Finish: Electro-Tin Plated, Installation Tool: Ratchet: MR8D94, MR8-33T-1, M8ND Tool With N10ET-9 Die, MR4 10M, MR18 Tool, Insulation Diameter (maximum): 0.209 IN, Wire Shroud: No, Color Code: Yellow, Conductor Type: Commercial/Military Stranded Copper, Wire Strip Length: 5/16 IN, Tongue Angle: Straight

## Product Details

### General

|                                      |   |
|--------------------------------------|---|
| Application                          | For High Vibration Applications Encountered In Aircraft And Aboard Ships As Well As Motor Lead Applications In Hospitals, Industrials And Generating Plants |
| Color Code                           | Yellow  |
| Connector Type                       | Terminal  |
| Insulation                           | Y   |
| Insulation Type                      | Nylon   |
| Material                             | Copper  |
| Physical Attribute - Number of Holes | 1   |
| Physical Attribute - Tongue Type     | Ring  |
| Plated                               | Y   |
| Plating Type                         | Tin   |
| Sub Brand                            | INSULUG   |
| Trade Name                           | INSULUG™  |
| Type                                 | YAEV, Heavy Duty  |
| UPC                                  | 781810564271  |
| UPC 12 Digit                         | 7818105642711   |

### Dimensions

|                                |         |
|--------------------------------|---------|
| Dimension - B Length fraction  | 3/10 in |
| Dimension - B Length inch      | 0.30 in |
| Dimension - Hole Size fraction | 10/37   |

|                                   |         |
|-----------------------------------|---------|
| Dimension - Hole Size inch        | 0.27 in |
| Dimension - Length Overall inch   | 1.30 in |
| Dimension - N inch                | 0.23 in |
| Dimension - Outside Diameter inch | 0.28 in |
| Dimension - P inch                | 0.09 in |
| Dimension - Pad Width inch        | 0.47 in |
| Dimension - Stud Size inch        | 1/4     |
| Dimension - Z inch                | 0.38 in |

## Electrical Ratings

|                   |       |
|-------------------|-------|
| Voltage - Maximum | 600 V |
|-------------------|-------|

## Conductor Related

|  |  |
|--|--|
| Conductor - Copper Str Aircraft Size       | AN 12;AN 10  |
| Conductor - Copper Str Aircraft Size Range | AN 12-AN 10  |
| Conductor - Copper Str Size                | 12;10  |
| Conductor - Copper Str Size Range          | 12-10  |
| Conductor Type                             | <ul style="list-style-type: none"> <li>• CU C Solid-Size</li> <li>• CU C Str-Size</li> </ul> |

## Certifications and Compliance

|                                    |  |
|------------------------------------|--|
| Certification - CSA Approved       | No   |
| Certification - ETL                | No   |
| Certification - UL Recognized      | No   |
| Certification - cULus              | No   |
| Industry Standard(s)               | <ul style="list-style-type: none"> <li>• UL486</li> <li>• Military Specified (Mil-Spec)</li> </ul> |
| Standards - Industry Standards Met | <ul style="list-style-type: none"> <li>• UL486</li> <li>• Military Specified (Mil-Spec)</li> </ul> |
| Standards - RoHS Compliance Status | CM   |
| UL Listed                          | Yes  |

## Logistics

|                       |     |
|-----------------------|-----|
| Minimum Pack Quantity | 500 |
|-----------------------|-----|

**For further technical assistance, please contact us**

**BURNDY Headquarters**  
47 East Industrial Park Drive  
Manchester, New Hampshire 03109

**Customer Service Hours:**  
8 AM - 8 PM Eastern Monday-Friday  
Emergency Service 24-hours/365 Days  
Phone: 1-800-346-4175  
1-603-647-5299 (International)