

Rigid/intermediate grade conduit fittings


Conduit bushed (chase) nipples, offset conduit nipples
Push plugs

Rigid fittings

CONDUIT BUSHED (CHASE) NIPPLES – MALLEABLE IRON & ZINC DIE CAST

Non-insulated and insulated threaded NPSM for rigid conduit and IMC

UL File No. E-19189



Applications:

- Used with a locknut to connect two boxes side by side or back to back
- Used with a locknut to connect fixture housing to continuous runs

Cat. # Non-insulated malleable iron	Cat. # Insulated malleable iron	Cat. # Non-insulated zinc die cast	Cat. # Insulated zinc die cast	Size	Unit qty.	Wt. lbs. per 100 Non-insulated malleable iron	Wt. lbs. per 100 Insulated malleable iron	Wt. lbs. per 100 Non-insulated zinc die cast
50		50D	1050DC	1/2"	50	3	3	4
51	1051	51D	1051DC	3/4"	25	8	4	5
52	1052	52D	1052DC	1"	10	13	11	10
53	1053	53D	1053DC	1 1/4"	10	19	19	11
54	1054	54D	1054DC	1 1/2"	10	30	30	20
55	1055	55D	1055DC	2"	10	37	37	30
56	1056	56D	1056DC	2 1/2"	5	68	72	40
57	1057	57D	1057DC	3"	5	92	96	49
58	1058	58D	1058DC	3 1/2"	1	130	113	68
59	1059	59D	1059DC	4"	1	200	187	70
60	1060			5"	1	350	350	
61	1061			6"	1	425	450	

- ① Steel.
- Ⓞ Not UL Listed.
- ⓄUL Listed for malleable iron versions.

OFFSET CONDUIT NIPPLES – ZINC DIE CAST

Features:

- Threaded NPSM for rigid conduit and IMC
- Used to offset the axis of raceways 3/4 of an inch

UL File No. E-19189



PUSH PLUGS – PLASTIC

Applications:

- Used to plug knockouts on enclosures to prevent moisture, dust and debris from entering the enclosure during shipment or install
- Plugs are wider than size listed to ensure secure connection in enclosure
- Temperature rating: 180°F to 200°F
- Tensile strength: 600-2300 PSI



Cat. # Zinc die cast	Size	Unit qty.	Wt. lbs. per 100
300DC	1/2"	25	24
301DC	3/4"	25	34
302DC	1"	10	49
303DC	1 1/4"	10	54
304DC	1 1/2"	5	40
305DC	2"	2	60

Cat. #	Size	Unit qty.	Wt. lbs. per 100
PPC 50	1/2"	100	1
PPC 75	3/4"	100	1
PPC 100	1"	50	1
PPC 125	1 1/4"	50	1
PPC 150	1 1/2"	25	1
PPC 200	2"	25	1
PPC 250	2 1/2"	100	2
PPC 300	3"	100	3
PPC 350	3 1/2"	50	6
PPC 400	4"	50	8


Rigid/intermediate grade conduit fittings

Snap-in blanks, reducing washers, concrete slab inserts

KNOCKOUT SNAP-IN BLANKS – STEEL

Applications:

- Used to plug knockouts in steel boxes
- Snap-in blanks press firmly into knockout, providing a secure connection



Cat. #	Size	Unit qty.	Wt. lbs. per 100
335	1/2"	100	2
336	3/4"	100	2
337	1"	50	2
338	1 1/4"	50	3
339	1 1/2"	50	5
340	2"	20	7

KNOCKOUT REDUCING WASHERS – STEEL

Applications:

- Used with steel boxes to reduce the knockout size
- Reducing washers press firmly into knockout, providing a secure connection

UL File No. E-23223



Cat. #	Size	Unit qty.	Wt. lbs. per 100
342	3/4" - 1/2"	100	1
343	1" - 1/2"	100	2
344	1" - 3/4"	100	2
345	1 1/4" - 1/2"	100	3
346	1 1/4" - 3/4"	100	2
347	1 1/4" - 1"	100	2
348	1 1/2" - 1/2"	50	5
349	1 1/2" - 3/4"	50	4
350S	1 1/2" - 1"	50	4
351	1 1/2" - 1 1/4"	50	3
352	2" - 1/2"	50	7
353	2" - 3/4"	50	7
354	2" - 1"	50	6
355	2" - 1 1/4"	50	5
356	2" - 1 1/2"	50	3
360	2 1/2" - 1/2"	25	7
361	2 1/2" - 3/4"	25	7
362	2 1/2" - 1"	25	7
363	2 1/2" - 1 1/4"	25	7
364	2 1/2" - 1 1/2"	25	7
365	2 1/2" - 2"	25	7
366	3" - 1"	25	14
367	3" - 1 1/4"	25	14
368	3" - 1 1/2"	25	14
369	3" - 2"	25	14
370 S	3" - 2 1/2"	25	14
371 Ⓞ	3 1/2" - 1 1/2"	25	25
372 Ⓞ	3 1/2" - 2"	25	25
373 Ⓞ	3 1/2" - 2 1/2"	25	25
374 Ⓞ	3 1/2" - 3"	25	25
375 Ⓞ	4" - 2"	25	35
376 Ⓞ	4" - 2 1/2"	25	35
377 Ⓞ	4" - 3"	25	35
378 Ⓞ	4" - 3 1/2"	25	35

Ⓞ Not UL Listed.

CONCRETE SLAB INSERTS – 90 DEGREE

Applications:

- For use with rigid and IMC
- For conduit installed in poured concrete slabs
- 90 degree design eliminates the need to bend conduit
- Provides flush threaded conduit hub for connecting rigid and IMC conduit and allows future access to conduit system
- Used in in-slab ceiling and floor poured applications

Standard Material:

- Zinc die cast



Cat. #	EMT	Unit Qty.	Wt. Lbs. Per 100
ESL75	3/4"	5	41
ESL100	1"	5	57

Dimensions (in inches):

Cat. #	A	B	C	D	E	F	G
ESL75	4.55	3.72	3.49	3.15	2.13	1.14	0.20
ESL100	4.68	3.84	3.46	3.10	2.44	1.47	0.19

