


NEUTRAL CONNECTORS

Neutral 225A


600 VAC



FEATURES

- These stacked neutral assemblies offer the ultimate in compact design and performance.
- Wire holes are stacked to minimize width. One-piece construction provides superior mechanical performance.
- Made from high strength 6061T-6 aluminum alloy.
- Options include a 350 MCM main lug and a high strength, glass-filled polyester mounting base for isolated mounting.
- Available in 12 to 42 wire holes (4-14 AWG).

RATINGS



CATALOG NO.	FIGURE NO.
1012	1
1012M	2
1012B	3
1012MB	4
1018	1
1018M	2
1018B	3
1018MB	4
1024	1
1024M	2
1024B	3
1024MB	4
1030	1
1030M	2
1030B	3
1030MB	4
1036	1
1036M	2
1036B	3
1036MB	4
1042	1
1042M	2
1042B	3
1042MB	4



NO. OF 4-14 AWG CIRCUITS	MAIN LUG SIZE	MOUNTING BASE	LENGTH	HEIGHT	WIDTH	STD. CTN. QTY.
12	none	no	2.068	0.875	1.500	1
12	350-6	no	2.193	1.375	1.500	1
12	none	yes	2.068	2.250	2.250	1
12	350-6	yes	2.193	2.750	2.250	1
18	none	no	3.132	0.875	1.500	1
18	350-6	no	3.257	1.375	1.500	1
18	none	yes	3.132	2.250	2.250	1
18	350-6	yes	3.257	2.750	2.250	1
24	none	no	4.196	0.875	1.500	1
24	350-6	no	4.321	1.375	1.500	1
24	none	yes	4.196	2.250	2.250	1
24	350-6	yes	4.321	2.750	2.250	1
30	none	no	5.260	0.875	1.500	1
30	350-6	no	5.385	1.375	1.500	1
30	none	yes	5.260	2.250	2.250	1
30	350-6	yes	5.385	2.750	2.250	1
36	none	no	6.324	0.875	1.500	1
36	350-6	no	6.449	1.375	1.500	1
36	none	yes	6.324	2.250	2.250	1
36	350-6	yes	6.449	2.750	2.250	1
42	none	no	7.388	0.875	1.500	1
42	350-6	no	7.513	1.375	1.500	1
42	none	yes	7.388	2.250	2.250	1
42	350-6	yes	7.513	2.750	2.250	1