

CONDUIT TAPPING & THREADING OIL

Cat. No. 15-112

Contains No Ozone Depleting Substances

USE FOR:

- Threading Rigid Steel
- Aluminum Conduit
- Cutting Tools
- Threading Tools
- Dies

ADVANTAGES:

- Speeds work.
- Prolongs tool life and cutting edge.
- Lubricates and cools the cutting point.
- Eliminates scoring and chatter marks.
- Prevents rust on newly machined parts.



CAUTION

Contains Combustible liquid.
(Read additional warnings and directions on this container.)

T&B Safety Data Sheet
Number SDS-00039

For product information call 800-816-7809
For emergencies only. Call CHEMTREC:
+1 703-741-5970

Thomas & Betts

A Member of the ABB Group

ONE
Net Contents:
1 Gallon / 7.6 lbs.

NOW! One Cutting Oil Does It All From Pipe and Conduit Threading to Machine Shop Applications...

Conduit Tapping & Threading Oil

This oil is a premium petroleum type cutting oil, chemically compounded to provide an excellent lubricant and coolant for heavy duty threading, cutting, tapping and drilling. It can be used on all types of metals both ferrous and non-ferrous for a wide range of metal cutting and threading operations.

NOTE: This container is made of break resistant material, however, some care should be taken when handling.

Applications:

- Threading
- Drilling
- Sawing
- Grinding
- Power Threaders
- Automatic Screw Machines
- Gear Cutters
- Grinders
- Tapping
- Cutting
- Milling
- General Machining
- Hand Threaders
- Turret Lathes
- Brochers

PRECAUTIONARY STATEMENT:

Prevention: Observe good industrial hygiene practices.

Response: Wash hands after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of waste and residues in accordance with local authority requirements.

SUPPLEMENTAL INFORMATION:

All components are on the U.S. EPA TSCA Inventory List. This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.



CAUTION



IN CASE OF A FIRE. Use dry chemical, Halon and carbon dioxide. Foam and water fog are effective but may cause frothing.

May Cause Skin or Eye Irritation. Avoid skin and eye contact. Wash thoroughly after handling.

Misuse of Container Can Be Hazardous. Empty containers can be dangerous if used to store toxic, flammable, or reactive materials. Do not pressurize or expose to open flame or head. Keep containers closed. Do not reuse before commercial cleaning.



WARRANTY

Limited Warranty Applies. Refer to:
www.tnb.com/ecpwarrenty for full warranty terms.

Supplier Identification:

© 2016 Thomas & Betts Corporation
8155 T&B Boulevard, Memphis,
Tennessee, 38125 - www.tnb.com

Made in U.S.A.